



## ALTRA 2000

### THE MOST RESILIENT SOLUTION

Since 1895, NIEDNER has been redefining the firefighting industry by creating lighter, more versatile lay-flat hoses to overcome the challenges firefighters face. What makes firefighters around the globe trust NIEDNER's ALTRA FIRE solutions is first and foremost the high quality and resiliency of the products. Our hoses are engineered to stand up under the most demanding applications, including intense heat and abrasion.

#### RUGGED AND RELIABLE

A durable attack or high-rise pack hose with a service test pressure rating of 400 PSIG (2800 kPa), perfect for all fireground operations. This 100% polyester double-jacket fire hose is lined with TPU elastomer and built for ruggedness, while remaining lightweight and compact. ALTRA 2000 has superior flow characteristics. The tight weave of the outer jacket resists snags, cuts, punctures and abrasion. The ENCAP™ treatment improves durability, reduces water absorption up to 40%, increases chemical resistance and allows for color options.

#### HIGHEST LEVEL OF QUALITY

NIEDNER maintains the highest levels of quality in the design, manufacturing, and testing of all our hose products. As a result, our solutions exceed the recognized international standards.

#### UNIQUE SERVICES

Our solutions have many advantages; quality, design, and engineering support, which is second to none.



Attack Hose



High-Rise Applications



Short lead-times



Rugged and Durable



Standard lengths:  
50/100 feet



Manufactured in accordance with NFPA 1961 standard

*Formally known as ULTRA2000*



## FEATURES

- Abrasion and puncture resistant
- Moderate kink resistance
- Ozone, age, mildew and bacteria resistant

## DESIGN

- Made of 100% polyester
- Lined with TPU elastomer
- ENCAP™ treatment

## ADVANTAGES

- Lightweight and compact
- Reduced water absorption up to 40%

Manufactured in North America.  
 Covered by NIEDNER's 10-year warranty.  
 All NIEDNER products are dried before shipping.

## TECHNICAL DATA

Diameter		Weight				Flat width		Thickness		Coil Diam.		Internal		Coupling		Pressure	
Inches	Spec #	50 ft., w/alum cplgs		100 ft., w/alum cplgs		All lengths		Layflat		50 ft., w/couplings		Diameter		Bowl size		Service test	
(mm)		lb	kg	lb	kg	in	cm	in	cm	in	cm	in	mm	in	mm	PSI	kPA
1 1/2" (38mm)	4115	14	6.35	26	11.79	2.875	7.30	0.25	0.64	20	50.8	1 11/16	43	1-15/16	49.2	400	2800
1 3/4" (45mm)	4117	16	7.26	30	13.61	3.125	7.94	0.28	0.71	20	50.8	1 13/16	46	2-1/16	52.4	400	2800
2" (51mm)	4120	19	8.62	37	16.78	3.375	8.57	0.28	0.71	20	50.8	2-1/16	52	2 5/16	58.7	400	2800
2 1/2" (64mm)	4125	24	10.89	46	20.87	4.5	11.43	0.28	0.71	21	53.34	2-3/4	70	3"	76.2	400	2800

AVAILABLE COLORS: White, Green, Red, Orange, Blue, Beige-Tan, Purple and Yellow

## CONTACT

sales@niedner.com  
 Tel: 800-567-2703  
 675 Merrill St., Coaticook, Quebec, J1A 2S2

**NIEDNER** | **ALTRA**

**NIEDNER-ALTRA.COM**