

NIEDNER DOUBLE-5™

THE MOST RESILIENT SOLUTION.

Since 1895, NIEDNER has been redefining the firefighting industry by creating lighter, more versatile lay-flat hoses to overcome the challenges firefighters face. What makes firefighters around the globe trust NIEDNER's solutions is first and foremost the high quality and resiliency of the products. Our hoses are engineered to stand up under the most demanding applications, including intense heat and abrasion.

COMBAT LARGE SCALE FIRES

DOUBLE- 5 is a unique lightweight 7 ¼" (184 mm) large diameter hose capable of significant water flow at higher pressures. The DOUBLE 5 is designed specifically to combat oil refinery and large storage tank fires.

HIGHEST LEVEL OF QUALITY

NIEDNER maintains the highest levels of quality in the design, manufacturing and testing of all our products. As a result, our solutions exceed the recognised international standards.

UNIQUE SERVICES

Our solutions have many advantages, including our unique services including engineering support.



Highly safe hose



Corrosion and maintenance-free



Short lead-times and quick to install



Reusable



Standard lengths: 50/100 feet



Increased resiliency



Commitment to the environment

NIEDNER ATTACK NIEDNER-ALTRA.COM



FEATURES

- Designed for use on rough terrain
- Ultimate abrasion and puncture resistance
- Mildew and bacteria resistant
- Capable of significant water flow at higher pressures
- Same water output as 2 x 5" hoses
- Lengths up to 500 feet

DESIGN

- Double jacket made of 100% polyester
- Lined with TPU elastomer for lightweight
- ENCAP™ treated for increased chemical resistance

OUR PRODUCT LINE CERTIFICATIONS

NIEDNER's solutions are certified by accredited independent institutes







ADVANTAGES

- Lightweight double jacket hose
- Flexible to -60°F (-51°C)
- Reduced water absorption up to 40%
- Does not need to be dried before storage
- Lay flat hose for space saving when rolled and stored

TECHNICAL DATA

Diameter		Weights**				Flat Width		Thickness		Coil Diam.**		Coupling	Internal		Pressure	
Inches	Spec	50 ft. w/Storz		100 ft. w/Storz		All lengths		Layflat		100 ft. w/Couplings		Standard with	Diameter		Service Test	
(mm)	#	Lbs.	Kgs.	Lbs.	Kgs.	in	cm	in	cm	in	cm		in	mm	PSI	kPA
7 1/4" (184mm)	50072	93	42.18	160	72.57	10.5	26.6	0.50	1.27	29"	73.7	6" LOCKING Storz	7.25	184.0	200	1380

 $[\]ensuremath{^{**}}$ Weights and Coil diameter may very with finished product

 ${\sf AVAILABLE\ COLORS:\ Beige-tan}$